



Printing date 20.10.2022 Version number 4 Revision: 20.10.2022

## I Identification of the hazardous chemical and of the supplier

- · Product identifier
- · Trade name: Transpoxy Finish 4.60 Part B
- · Article number: 4.60 (B)
- · Recommended use of the chemical and restrictions on use No further relevant information available.
- · Application of the substance / the mixture Coating material
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

KOSSAN PAINT (M) SDN. BHD.

1, Jalan Koporat 1/KU9, Taman

Perindustrian Meru, 42200 Kapar,

Selangor Darul Ehsan, Malaysia.

Further information obtainable from:

Product safety department.

lsk@kossanpaint.com.my

· Emergency telephone number:

Manufacturer/supplier

603-33922799

### 2 Hazard identification

· Classification of the substance or mixture



Flam. Liq. 3 H226 Flammable liquid and vapour.



Acute Tox. 4 H302 Harmful if swallowed.

Acute Tox. 4 H332 Harmful if inhaled.

Skin Irrit. 2 H315 Causes skin irritation.

- · Label elements
- · GHS label elements The product is classified and labelled according to the Globally Harmonised System (GHS).
- · Hazard pictograms GHS02, GHS07
- · Signal word Warning
- · Hazard statements

Flammable liquid and vapour.

Harmful if swallowed or inhaled.

Causes skin irritation.

· Precautionary statements

*Keep away from heat/sparks/open flames/hot surfaces – No smoking.* 

Use explosion-proof electrical/ventilating/lighting equipment.

Avoid breathing dust/fume/ gas/mist/vapours/spray.

Wear protective gloves/protective clothing/eye protection/face protection.

IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.

(Contd. on page 2)

Printing date 20.10.2022 Version number 4 Revision: 20.10.2022

Trade name: Transpoxy Finish 4.60 Part B

(Contd. of page 1)

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

### 3 Composition and information of the ingredients of the hazardous chemical

- · Chemical characterisation: Mixtures
- Description: Mixture of substances listed below with nonhazardous additions.

· Dangerou	s components:	
1330-20-7	xylene	≥10-<30%
	♦ Flam. Liq. 3, H226; ♦ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	
71-36-3	butan-1-ol	≥3-<8.5%
	♠ Flam. Liq. 3, H226; ♠ Eye Dam. 1, H318; ♠ Acute Tox. 4, H302; Skin Irrit. 2, H315; STOT SE 3, H335-H336	

<sup>·</sup> Additional information: For the wording of the listed hazard phrases refer to section 16.

#### 4 First-aid measures

- · Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist. In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed

No further relevant information available.

### 5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

### 6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.

(Contd. on page 3)

Printing date 20.10.2022 Version number 4 Revision: 20.10.2022

Trade name: Transpoxy Finish 4.60 Part B

(Contd. of page 2)

• Environmental precautions: Do not allow to enter sewers/ surface or ground water.

Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

#### 7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- · Specific end use(s) No further relevant information available.

#### 8 Exposure controls and personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · Control parameters
- Ingredients with limit values that require monitoring at the workplace:

### 71-36-3 butan-1-ol (≥3-<8.5%)

PEL (Malaysia) Ceiling limit: 152 mg/m³, 50 ppm

- · Additional information: The lists valid during the making were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

(Contd. on page 4)

(Contd. of page 3)

## Safety Data Sheet according to P.U.(A) 310/2013

Printing date 20.10.2022 Version number 4 Revision: 20.10.2022

Trade name: Transpoxy Finish 4.60 Part B

#### · Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

#### · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

0 D1	1 1	7	1	
9 Physical	and	chemica	l nro	nortios
) I hysical	turrett (	chemitem	, pro	Derites

· General Information

· Appearance:

Form: Liquid

Colour: Amber coloured
Odour: Characteristic
Odour threshold: Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/freezing point Undetermined.

Initial boiling point and boiling range Undetermined.

· Flash point: 27 °C

· Flammability (solid, gas) Not applicable.

• Decomposition temperature: Not determined.

· Auto-ignition temperature Product is not selfigniting.

• Explosive properties: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· Explosion limits:

Lower: Not determined.
Upper: Not determined.

· Vapour pressure: Not determined.

Density at 20 °C: 0.93 g/cm<sup>3</sup>

(Contd. on page 5)

Printing date 20.10.2022 Version number 4 Revision: 20.10.2022

Trade name: Transpoxy Finish 4.60 Part B

	(Contd. of page
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water	Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Other information	No further relevant information available.

## 10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

### 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity
- · LD/LC50 values relevant for classification:

1330-20	•	
Oral	<i>LD50</i>	4,300 mg/kg (r

Dermal LD50 2,000 mg/kg (rabbit)

- Primary irritant effect:
- · Skin corrosion or irritation Irritant to skin and mucous membranes.
- · Serious eye damage or eye irritation Irritating effect.
- Respiratory / skin sensitization No sensitising effects known.
- · Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Harmful

Irritant

### 12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.

(Contd. on page 6)

Printing date 20.10.2022 Version number 4 Revision: 20.10.2022

Trade name: Transpoxy Finish 4.60 Part B

(Contd. of page 5)

- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

## 13 Disposal information

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

Transportation information		
UN-Number ADR, IMDG, IATA	UN1263	
UN proper shipping name ADR IMDG, IATA	1263 PAINT PAINT	
Transport hazard class(es)  ADR, IMDG, IATA		
Class Label	3 Flammable liquids. 3	
Packing group ADR, IMDG, IATA	III	
Environmental hazards: Marine pollutant:	No	
Special precautions for user EMS Number:	Warning: Flammable liquids. F-E, <u>S-E</u>	
Transport in bulk according to Annex I and the IBC Code	<b>I of Marpol</b> Not applicable.	
UN "Model Regulation":	UN 1263 PAINT, 3, III	

MY

Printing date 20.10.2022 Version number 4 Revision: 20.10.2022

Trade name: Transpoxy Finish 4.60 Part B

(Contd. of page 6)

## 15 Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

· EHS reference list

1330-20-7 xylene

71-36-3 butan-1-ol

- GHS label elements The product is classified and labelled according to the Globally Harmonised System (GHS).
- · Hazard pictograms GHS02, GHS07
- · Signal word Warning
- · Hazard statements

Flammable liquid and vapour.

Harmful if swallowed or inhaled.

Causes skin irritation.

· Precautionary statements

*Keep away from heat/sparks/open flames/hot surfaces – No smoking.* 

*Use explosion-proof electrical/ventilating/lighting equipment.* 

Avoid breathing dust/fume/ gas/mist/vapours/spray.

Wear protective gloves/protective clothing/eye protection/face protection.

IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Product safety department.
- · Contact: Mr. S.K. Lim
- · Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity - oral - Category 4

Skin Irrit. 2: Skin corrosion or irritation – Category 2

Eye Dam. 1: Serious eye damage or eye irritation – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

\* Data compared to the previous version altered.

MY