

## Safety Data Sheet

according to P.U.(A) 310/2013

Printing date 28.04.2021

Version number 1

Revision: 28.04.2021

### 1 Identification of the hazardous chemical and of the supplier

- **Product identifier**
- **Trade name:** Kossan 2K Auto Refinish Primer KAR-1000P Part B
- **Article number:** KAR-1000P (B)
- **Recommended use of the chemical and restrictions on use** No further relevant information available.
- **Application of the substance / the mixture** Coating material
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
 KOSSAN PAINT (M) SDN. BHD.  
 1, Jalan Koporat 1/KU9, Taman  
 Perindustrian Meru, 42200 Kapar,  
 Selangor Darul Ehsan, Malaysia.
- **Further information obtainable from:**  
 Product safety department.  
 lsk@kossanpaint.com.my
- **Emergency telephone number:**  
 Manufacturer/supplier  
 603-33922799

### 2 Hazard identification

- **Classification of the substance or mixture**



Flam. Liq. 2 H225      Highly flammable liquid and vapour.



Resp. Sens. 1 H334      May cause allergic or asthma symptoms or breathing difficulties if inhaled.  
 Carc. 2 H351      Suspected of causing cancer.  
 STOT RE 2 H373      May cause damage to organs through prolonged or repeated exposure.



Acute Tox. 4 H332      Harmful if inhaled.  
 Skin Irrit. 2 H315      Causes skin irritation.  
 Eye Irrit. 2 H319      Causes serious eye irritation.  
 Skin Sens. 1 H317      May cause allergic skin reaction.  
 STOT SE 3 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

- **Label elements**
- **GHS label elements** The product is classified and labelled according to the Globally Harmonised System (GHS).
- **Hazard pictograms** GHS02, GHS07, GHS08

(Contd. on page 2)

**Safety Data Sheet**  
according to P.U.(A) 310/2013

Printing date 28.04.2021

Version number 1

Revision: 28.04.2021

**Trade name: Kossan 2K Auto Refinish Primer KAR-1000P Part B**

(Contd. of page 1)

· **Signal word** *Danger*

· **Hazard-determining components of labelling:**

*diphenylmethanediisocyanate, isomeres and homologues*  
*m-tolylidene diisocyanate*

· **Hazard statements**

*Highly flammable liquid and vapour.*

*Harmful if inhaled.*

*Causes skin irritation.*

*Causes serious eye irritation.*

*May cause allergic or asthma symptoms or breathing difficulties if inhaled.*

*May cause allergic skin reaction.*

*Suspected of causing cancer.*

*May cause respiratory irritation. May cause drowsiness or dizziness.*

*May cause damage to organs through prolonged or repeated exposure.*

· **Precautionary statements**

*Keep away from heat/sparks/open flames/hot surfaces – No smoking.*

*Use explosion-proof electrical/ ventilating/lighting equipment.*

*IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.*

*IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.*

*Continue rinsing.*

*Store locked up.*

*Dispose of contents/container in accordance with local/regional/national/international regulations.*

· **Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

### 3 Composition and information of the ingredients of the hazardous chemical

· **Chemical characterisation: Mixtures**

· **Description:** Mixture of substances listed below with nonhazardous additions.

· **Dangerous components:**

123-86-4	<i>n-butyl acetate</i> ⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336	≥20-<50%
9016-87-9	<i>diphenylmethanediisocyanate, isomeres and homologues</i> ⚠ Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; ⚠ Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335	≥10-<40%
141-78-6	<i>ethyl acetate</i> ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336	≥10-<13%
26471-62-5	<i>m-tolylidene diisocyanate</i> ⚠ Acute Tox. 2, H330; ⚠ Resp. Sens. 1, H334; Carc. 2, H351; ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335; Aquatic Chronic 3, H412	≥0.1-<0.3%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

MY

(Contd. on page 3)

# Safety Data Sheet

## according to P.U.(A) 310/2013

Printing date 28.04.2021

Version number 1

Revision: 28.04.2021

**Trade name: Kossan 2K Auto Refinish Primer KAR-1000P Part B**

(Contd. of page 2)

### 4 First-aid measures

- **Description of first aid measures**
- **General information:**  
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:**  
Supply fresh air and to be sure call for a doctor.  
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**  
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

### 5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** CO<sub>2</sub>, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

### 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**  
Do not allow product to reach sewage system or any water course.  
Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.  
Do not flush with water or aqueous cleansing agents
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

### 7 Handling and storage

- **Handling:**
- **Precautions for safe handling**  
Ensure good ventilation/exhaustion at the workplace.  
Prevent formation of aerosols.

(Contd. on page 4)

MY

# Safety Data Sheet

according to P.U.(A) 310/2013

Printing date 28.04.2021

Version number 1

Revision: 28.04.2021

**Trade name: Kossan 2K Auto Refinish Primer KAR-1000P Part B**

(Contd. of page 3)

- **Information about fire - and explosion protection:**  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**  
Keep container tightly sealed.  
Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

## 8 Exposure controls and personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
- **Control parameters**

<b>Ingredients with limit values that require monitoring at the workplace:</b>	
<b>123-86-4 n-butyl acetate (≥20-&lt;50%)</b>	
PEL (Malaysia)	Long-term value: 713 mg/m <sup>3</sup> , 150 ppm
<b>141-78-6 ethyl acetate (≥10-&lt;13%)</b>	
PEL (Malaysia)	Long-term value: 1440 mg/m <sup>3</sup> , 400 ppm

- **Additional information:** The lists valid during the making were used as basis.

- **Exposure controls**

- **Personal protective equipment:**

- **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

- **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)

# Safety Data Sheet

according to P.U.(A) 310/2013

Printing date 28.04.2021

Version number 1

Revision: 28.04.2021

Trade name: **Kossan 2K Auto Refinish Primer KAR-1000P Part B**

(Contd. of page 4)

· **Eye protection:**

Tightly sealed goggles

## 9 Physical and chemical properties

· **Information on basic physical and chemical properties**· **General Information**· **Appearance:**

· <b>Form:</b>	Liquid
· <b>Colour:</b>	Colourless to yellow
· <b>Odour:</b>	Characteristic
· <b>Odour threshold:</b>	Not determined.

· **pH-value:** Not determined.· **Change in condition**

· <b>Melting point/freezing point</b>	Undetermined.
· <b>Initial boiling point and boiling range</b>	Undetermined.

· **Flash point:** 5 °C· **Flammability (solid, gas)** Not applicable.· **Decomposition temperature:** Not determined.· **Auto-ignition temperature** Product is not selfigniting.· **Explosive properties:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.· **Explosion limits:**

· <b>Lower:</b>	1.2 Vol %
· <b>Upper:</b>	7.5 Vol %

· **Vapour pressure at 20 °C:** 10.7 hPa· **Density at 20 °C:** 1.01 g/cm<sup>3</sup>· **Relative density** Not determined.· **Vapour density** Not determined.· **Evaporation rate** Not determined.· **Solubility in / Miscibility with water:**

Not miscible or difficult to mix.

· **Partition coefficient: n-octanol/water** Not determined.· **Viscosity:**

· <b>Dynamic:</b>	Not determined.
· <b>Kinematic at 20 °C:</b>	13 s (DIN 53211/4)

· **Other information** No further relevant information available.

## 10 Stability and reactivity

· **Reactivity** No further relevant information available.

(Contd. on page 6)

# Safety Data Sheet

## according to P.U.(A) 310/2013

Printing date 28.04.2021

Version number 1

Revision: 28.04.2021

**Trade name: Kossan 2K Auto Refinish Primer KAR-1000P Part B**

(Contd. of page 5)

- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

### 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity**
- **Primary irritant effect:**
- **Skin corrosion or irritation** Irritant to skin and mucous membranes.
- **Serious eye damage or eye irritation** Irritating effect.
- **Respiratory / skin sensitization**  
Sensitisation possible through inhalation.  
Sensitisation possible through skin contact.
- **Additional toxicological information:**  
The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:  
Harmful  
Irritant

### 12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behaviour in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**  
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water  
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

### 13 Disposal information

- **Waste treatment methods**
- **Recommendation**  
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

MY

(Contd. on page 7)

# Safety Data Sheet

according to P.U.(A) 310/2013

Printing date 28.04.2021


Version number 1

Revision: 28.04.2021

Trade name: **Kossan 2K Auto Refinish Primer KAR-1000P Part B**

(Contd. of page 6)

## 14 Transportation information

<ul style="list-style-type: none"> <li>· UN-Number</li> <li>· ADR, IMDG, IATA</li> </ul>	UNI263
<ul style="list-style-type: none"> <li>· UN proper shipping name</li> <li>· ADR</li> <li>· IMDG, IATA</li> </ul>	1263 PAINT PAINT
<ul style="list-style-type: none"> <li>· Transport hazard class(es)</li> <li>· ADR, IMDG, IATA</li> </ul>	<div style="text-align: center;">  </div>
<ul style="list-style-type: none"> <li>· Class</li> <li>· Label</li> </ul>	3 Flammable liquids. 3
<ul style="list-style-type: none"> <li>· Packing group</li> <li>· ADR, IMDG, IATA</li> </ul>	III
<ul style="list-style-type: none"> <li>· Environmental hazards:</li> <li>· Marine pollutant:</li> </ul>	No
<ul style="list-style-type: none"> <li>· Special precautions for user</li> <li>· EMS Number:</li> </ul>	Warning: Flammable liquids. F-E, S-E
<ul style="list-style-type: none"> <li>· Transport in bulk according to Annex II of Marpol and the IBC Code</li> </ul>	Not applicable.
<ul style="list-style-type: none"> <li>· UN "Model Regulation":</li> </ul>	UN 1263 PAINT, 3, III

## 15 Regulatory information

<ul style="list-style-type: none"> <li>· Safety, health and environmental regulations/legislation specific for the substance or mixture</li> </ul>	
<ul style="list-style-type: none"> <li>· EHS reference list</li> </ul>	
123-86-4	n-butyl acetate
141-78-6	ethyl acetate
26471-62-5	m-tolylidene diisocyanate
<ul style="list-style-type: none"> <li>· GHS label elements The product is classified and labelled according to the Globally Harmonised System (GHS).</li> <li>· Hazard pictograms GHS02, GHS07, GHS08</li> <li>· Signal word Danger</li> </ul>	
<ul style="list-style-type: none"> <li>· Hazard-determining components of labelling: diphenylmethanediisocyanate, isomeres and homologues m-tolylidene diisocyanate</li> <li>· Hazard statements Highly flammable liquid and vapour. Harmful if inhaled. Causes skin irritation. Causes serious eye irritation. May cause allergic or asthma symptoms or breathing difficulties if inhaled. May cause allergic skin reaction. Suspected of causing cancer. May cause respiratory irritation. May cause drowsiness or dizziness.</li> </ul>	

(Contd. on page 8)



# Safety Data Sheet

## according to P.U.(A) 310/2013

Printing date 28.04.2021

Version number 1

Revision: 28.04.2021

**Trade name: Kossan 2K Auto Refinish Primer KAR-1000P Part B**

(Contd. of page 7)

May cause damage to organs through prolonged or repeated exposure.

· **Precautionary statements**

Keep away from heat/sparks/open flames/hot surfaces – No smoking.

Use explosion-proof electrical/ ventilating/lighting equipment.

IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Directive 2012/18/EU**

· **Named dangerous substances - ANNEX I** None of the ingredients is listed.

· **Seveso category P5c** FLAMMABLE LIQUIDS

· **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t

· **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Product safety department.

· **Contact:** Mr. S.K. Lim

· **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 2: Acute toxicity - oral – Category 2

Acute Tox. 4: Acute toxicity - oral – Category 4

Skin Irrit. 2: Skin corrosion or irritation – Category 2

Eye Irrit. 2: Serious eye damage or eye irritation – Category 2

Resp. Sens. 1: Respiratory sensitization – Category 1

Skin Sens. 1: Skin sensitization – Category 1

Carc. 2: Carcinogenicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - chronic hazard – Category 3

MY