

*

*

MY

Safety Data Sheet according to P.U.(A) 310/2013

Printing date 28.04.2021

Version number 1

Revision: 28.04.2021

Product identif	ler
Trade name: <u>T</u>	ranspoxy MasterBond KPC-466 Part B
	: KPC-466 (B) use of the chemical and restrictions on use No further relevant information available. the substance / the mixture Coating material
Manufacturer/ KOSSAN PAIN 1,Jalan Kopora Perindustrian M	upplier of the safety data sheet Supplier: T (M) SDN. BHD. et 1/KU9, Taman Meru, 42200 Kapar, ' Ehsan, Malaysia.
Product safety a lsk@kossanpain	nt.com.my phone number:
Hazard iden	tification
Hazard iden	
	of the substance or mixture
Classification of	of the substance or mixture
Classification of flame Flam. Liq. 3	of the substance or mixture
Classification of flame Flam. Liq. 3	of the substance or mixture P H226 Flammable liquid and vapour.
Classification of flame Flam. Liq. 3	of the substance or mixture H226 Flammable liquid and vapour. h hazard H361 Suspected of damaging fertility or the unborn child.
Classification of flame Flam. Liq. 3 Flam. Liq. 3 Repr. 2	of the substance or mixture H226 Flammable liquid and vapour. h hazard H361 Suspected of damaging fertility or the unborn child.
Classification of flame Flam. Liq. 3 Flam. Liq. 3 healt Repr. 2 corre	of the substance or mixture H226 Flammable liquid and vapour. h hazard H361 Suspected of damaging fertility or the unborn child.
Classification of flame Flam. Liq. 3 Flam. Liq. 3 healt Repr. 2 Skin Corr. 1 Eye Dam. 1	of the substance or mixture H226 Flammable liquid and vapour. h hazard H361 Suspected of damaging fertility or the unborn child. psion H314 Causes severe skin burns and eye damage.
Classification of flame Flam. Liq. 3 Flam. Liq. 3 healt Repr. 2 Skin Corr. 1 Eye Dam. 1	onment

Revision: 28.04.2021

Printing date 28.04.2021 Version number 1 Trade name: Transpoxy MasterBond KPC-466 Part B (Contd. of page 1) Acute Tox. 4 H302 Harmful if swallowed. Skin Sens. 1 H317 May cause allergic skin reaction. · Label elements • GHS label elements The product is classified and labelled according to the Globally Harmonised System (GHS). · Hazard pictograms GHS02, GHS05, GHS07, GHS08, GHS09 · Signal word Danger · Hazard-determining components of labelling: xylene 4-nonylphenol, branched 3,6-diazaoctanethylenediamin iso-butanol · Hazard statements Flammable liquid and vapour. Harmful if swallowed. Causes severe skin burns and eye damage. May cause allergic skin reaction. Suspected of damaging fertility or the unborn child. Very toxic to aquatic life with long lasting effects. · Precautionary statements IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor. Specific treatment (see on this label). Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. • Other hazards · Results of PBT and vPvB assessment • **PBT:** Not applicable. · vPvB: Not applicable. 3 Composition and information of the ingredients of the hazardous chemical · Chemical characterisation: Mixtures • Description: Mixture of substances listed below with nonhazardous additions. · Dangerous components

· Dangerous	1	
1330-20-7	xylene	≥10-<30%
	🚸 Flam. Liq. 3, H226; 🚸 Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	
84852-15-3	4-nonylphenol, branched	≥5-<25%
78-83-1	iso-butanol	≥10-<12%
	♦ Flam. Liq. 3, H226; ♦ Eye Dam. 1, H318; ♦ Skin Irrit. 2, H315; STOT SE 3, H335-H336	
71-36-3	butan-1-ol	<i>≥</i> 3-<7%
		_
	()	Contd. on page 3)

Printing date 28.04.2021

Version number 1

Revision: 28.04.2021

Trade name: Transpoxy MasterBond KPC-466 Part B

	(0	Contd. of page 2)
90-72-2	2,4,6-tris(dimethylaminomethyl)phenol	<5.5%
	Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2, H319	
108-91-8	cyclohexylamine	<i>≥</i> 3-<3.5%
	(*) $Cyclonexylamine (*) Flam. Liq. 3, H226; (*) Repr. 2, H361; (*) Skin Corr. 1, H314; (*) Acute Tox. 4, H302; Acute Tox. 4, H312$	
112-24-3	3,6-diazaoctanethylenediamin	<i>≥</i> 1-<1.7%
	Skin Corr. 1, H314; () Acute Tox. 4, H312; Skin Sens. 1, H317; Aquatic Chronic 3, H412	
Additional information: For the wording of the listed hazard phrases refer to section 16.		

4 First-aid measures

- · Description of first aid measures
- · General information:
- Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- After swallowing: Call for a doctor immediately.
- Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures
- Wear protective equipment. Keep unprotected persons away.
- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up:
- Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

- Do not flush with water or aqueous cleansing agents
- · Reference to other sections

See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment.

(Contd. on page 4)

MY

Printing date 28.04.2021

Version number 1

Revision: 28.04.2021

(Contd. of page 3)

Trade name: Transpoxy MasterBond KPC-466 Part B

See Section 13 for disposal information.

7 Handling and storage

· Handling:

- **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- *Information about fire and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.*
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls and personal protection

- Additional information about design of technical facilities: No further data; see item 7.
- · Control parameters

· Ingredients with limit values that require monitoring at the workplace:

78-83-1 iso-butanol (≥10-<12%)

PEL (Malaysia) Long-term value: 152 mg/m³, 50 ppm

71-36-3 butan-1-ol (≥3-<7%)

PEL (Malaysia) Ceiling limit: 152 mg/m³, 50 ppm (kulit)

108-91-8 cyclohexylamine (≥3-<3.5%)

PEL (Malaysia) Long-term value: 41 mg/m³, 10 ppm

• Additional information: The lists valid during the making were used as basis.

· Exposure controls

- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

- Do not inhale gases / fumes / aerosols.
- Avoid contact with the eyes and skin.

• Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



(Contd. on page 5)

MY

Printing date 28.04.2021

Version number 1

Revision: 28.04.2021

Trade name: Transpoxy MasterBond KPC-466 Part B

(Contd. of page 4)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation · *Material of gloves*

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- Penetration time of glove material
- The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

General Information	
Appearance:	
Form:	Liquid
Colour:	Clear
Odour:	Characteristic
Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/freezing point	Undetermined.
Initial boiling point and boiling range	Undetermined.
Flash point:	27 °C
Flammability (solid, gas)	Not applicable.
Decomposition temperature:	Not determined.
Auto-ignition temperature	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive air/vapou mixtures are possible.
Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
Vapour pressure:	Not determined.
Density at 20 °C:	0.91 g/cm^3
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.

_____МҮ

Printing date 28.04.2021

Version number 1

Revision: 28.04.2021

Trade name: Transpoxy MasterBond KPC-466 Part B

		(Contd. of page 5)
· Partition coefficient: n-octanol/water	Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic at 20 °C:	16 s (DIN 53211/4)	
Other information	No further relevant information available.	

10 Stability and reactivity

· Reactivity No further relevant information available.

- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- *Conditions to avoid* No further relevant information available.
- Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

· Information on toxicological effects

· Acute toxicity

· LD/LC50 values relevant for classification:

1330-20-7 xylene

Oral LD50 4,300 mg/kg (rat)

Dermal LD50 2,000 mg/kg (rabbit)

108-91-8 cyclohexylamine

Oral LD50 156 mg/kg (rat)

Dermal LD50 277 mg/kg (rabbit)

- · Primary irritant effect:
- Skin corrosion or irritation Irritant to skin and mucous membranes.
- · Serious eye damage or eye irritation Irritating effect.
- · Respiratory / skin sensitization No sensitising effects known.
- Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version: Harmful

Irritant

12 Ecological information

· Toxicity

- · Aquatic toxicity: No further relevant information available.
- Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- *Mobility in soil* No further relevant information available.

(Contd. on page 7)

MY

Printing date 28.04.2021

Version number 1

Revision: 28.04.2021

(Contd. of page 6)

Trade name: Transpoxy MasterBond KPC-466 Part B

• Additional ecological information:

· General notes:

Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water Do not allow product to reach ground water, water course or sewage system, even in small quantities. Danger to drinking water if even extremely small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- **vPvB:** Not applicable.
- Other adverse effects No further relevant information available.

13 Disposal information

· Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.

UN-Number ADR, IMDG, IATA	UN1263
UN proper shipping name ADR IMDG, IATA	1263 PAINT, ENVIRONMENTALLY HAZARDOUS PAINT
Transport hazard class(es)	
ADR, IMDG, IATA	
Class Label	3 Flammable liquids. 3
Packing group ADR, IMDG, IATA	111
Environmental hazards: Marine pollutant:	Product contains environmentally hazardous substances: nonylphenol, branched No
Special precautions for user EMS Number:	Warning: Flammable liquids. F-E, <u>S-E</u>
Transport in bulk according to Annex I and the IBC Code	I of Marpol Not applicable.
UN "Model Regulation":	UN 1263 PAINT, 3, III, ENVIRONMENTAL HAZARDOUS

(Contd. on page 8)

Printing date 28.04.2021

Version number 1

Revision: 28.04.2021

Trade name: Transpoxy MasterBond KPC-466 Part B

(Contd. of page 7)

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· EHS reference list

All ingredients are listed.

- GHS label elements The product is classified and labelled according to the Globally Harmonised System (GHS).
- · Hazard pictograms GHS02, GHS05, GHS07, GHS08, GHS09
- Signal word Danger

· Hazard-determining components of labelling:

xylene

4-nonylphenol, branched 3,6-diazaoctanethylenediamin iso-butanol

· Hazard statements

Flammable liquid and vapour.

- Harmful if swallowed.
- Causes severe skin burns and eye damage.
- May cause allergic skin reaction.
- Suspected of damaging fertility or the unborn child.
- Very toxic to aquatic life with long lasting effects.

· Precautionary statements

IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor. Specific treatment (see on this label). Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations.

· Directive 2012/18/EU

- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category

E2 Hazardous to the Aquatic Environment P5c FLAMMABLE LIQUIDS

- Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Product safety department.

· Contact: Mr. S.K. Lim

• Abbreviations and acronyms:

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

(Contd. on page 9)

MY

M١

Safety Data Sheet according to P.U.(A) 310/2013

Printing date 28.04.2021

Version number 1

Revision: 28.04.2021

Trade name: Transpoxy MasterBond KPC-466 Part B

	(Contd. of page 8)
LD50: Lethal dose, 50 percent	
PBT: Persistent, Bioaccumulative and Toxic	
vPvB: very Persistent and very Bioaccumulative	
Flam. Liq. 3: Flammable liquids – Category 3	
Acute Tox. 4: Acute toxicity - oral – Category 4	
Skin Corr. 1: Skin corrosion or irritation – Category 1	
Skin Irrit. 2: Skin corrosion or irritation – Category 2	
Eye Dam. 1: Serious eye damage or eye irritation – Category 1	
Eye Irrit. 2: Serious eye damage or eye irritation – Category 2	
Skin Sens. 1: Skin sensitization – Category I	
Repr. 2: Reproductive toxicity – Category 2	
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3	
Aquatic Acute 1: Hazardous to the aquatic environment - acute hazard – Category 1	
Aquatic Chronic 1: Hazardous to the aquatic environment - chronic hazard – Category 1	
Aquatic Chronic 3: Hazardous to the aquatic environment - chronic hazard – Category 3	
* Data compared to the previous version altered.	