



PRODUCT DATA SHEET

KOSETCHING PVB PRIMER KPC-102

KOSETCHING PVB PRIMER KPC-102

(SINGLE PACK POLYVINYL BUTYRAL ETCHING PRIMER)

DESCRIPTION

A single pack polyvinylbutyral etch primer with suitable anticorrosive pigment and phosphoric acid. It is suitable as pre-treatment primer for steel and non-ferrous metals such as aluminium and galvanized substrates. It can be overcoated with all paints except for inorganic zinc silicates.

PHYSICAL PROPERTIES

Colour	: Light Grey & Black
Specific gravity	: $1.00 \pm 0.02 \text{ gm/cm}^3$
Solid content	: 11 by volume.
Voc	: 726 gr/litre
Touch dry	: 3 minutes (at 30°C)
Dry to handle	: 15 minutes (at 30°C)
Recoating time	: Min. 2 hours.
Flash point	: >7°C

SURFACE PREPARATION

Steel surfaces : Oil and grease should be removed by solvent cleaning according to SSPC-SP1. Remove weld spatter and smooth weld seams and sharp edges as applicable. Abrasive blasting: min. Sa2 – ISO 8501:1.

Aluminimu : Solvent cleaning according to SSPC-SP1 followed by light blast cleaning with a fine grade abrasive or by chemical etching.

Galvanized / Zinc primed steel : Remove zinc salts by power- or hand tool cleaning. Solvent cleaning according to SSPC-SP1.

MIXING / APPLICATION DATA

Guiding data Airless Spray : Pressure at nozzle :min.150 bar. Nozzle size : 0.20-0.40mm.
Spray angle 40-80 degrees.

KOSSAN PAINT (M) SDN.BHD

1 Jalan Koporat 1/KU 9, Taman Perindustrian Meru, 42200 Kapar, Selangor D.E. Malaysia
Tel: 603-33922799; Fax: 603-33923799; e-mail: lsk@kossanpaint.com.my; Website: www.kossanpaint.com



PRODUCT DATA SHEET

KOSETCHING PVB PRIMER KPC-102

Volume of thinner required : 5-10%

Application by Air Spray (Conventional Spray) : Pressure at nozzle : 3-4 bar. Nozzle size : 1.0-1.5mm
Volume of thinner required : 10-15%

Application by Brush / Roller : Suitable
Volume of thinner required : 5-10%

Thinner / Cleaner : Kossan PVB thinner 6.02

Recommended wft : 1 coat x 90.91 μm

Recommended dft : 1 coat x 10 μm

CONDITIONS

Humidity : below 90% R.H.

Temperature of the paint before application : min.10°C, max. 40°C.

Substrate temperature min. 5°C, max. 50°C. The temperature of the substrate should be at least 3°C above the dew point of the air. Air temperature and relative humidity should be measured in the vicinity of the substrate.

THEORITICAL COVERAGE & PACKING SIZE

Coverage : 11.0 m²/litre per coat.

Packing Size : 5 litre

STORAGE

KOSETCHING PVB PRIMER KPC-102 have a minimum self-life of 12 months at cool and dry place.
Containers must be kept tightly closed.

HEALTY & SAFETY

Avoid skin and eyes contact by wearing suitable overalls, gloves, goggles, etc. Spillage on the skin should immediately be removed by thorough washing with water and soap. Eyes should be well flushed with water and medical attention sought immediately.

DISCLAIMER

The information in this data sheet is provided to the best of our knowledge. However, we have no control over either quality or condition of the substrate and other factor affecting the use and application of this product. Therefore, we cannot accept any liability whatsoever or howsoever arising from the performance of the product or for any loss or damage arising from the use of this product. We reserve the right to change the product data without notice.

KOSSAN PAINT (M) SDN.BHD

1 Jalan Koporat 1/KU 9, Taman Perindustrian Meru, 42200 Kapar, Selangor D.E. Malaysia
Tel: 603-33922799; Fax: 603-33923799; e-mail: lsk@kossanpaint.com.my; Website: www.kossanpaint.com